## NSN 5305-01-155-9784

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-155-9784 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.245 inches and 0.375 inches **Fastener Length:** Between 0.345 inches and 0.375 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.187 inches and 0.190 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Color: Black Material: Steel **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 class 1 military specification single treatment response **Thread Series Designator:** Unrc **Specification Data:** 

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

## NSN 5305-01-155-9784

Socket Head Cap Screw - Page 2 of 2



ı	Ini	4	Ωf	RЛ		۰.	ıre	
ι	JNI	IT '	UI.	IVI	ea	รเ	ıre	

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.