NSN 5305-01-156-5119

Panel Screw Assembly - Page 1 of 2





Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.250 inches

Fastener Length:

Between 1.088 inches and 1.128 inches

Head Style:

Pan

Head Diameter:

Between 0.357 inches and 0.373 inches

Head Height:

Between 0.122 inches and 0.133 inches

Internal Drive Style:

Cross recess type 1

Material Accommodated Thickness:

Between 0.188 inches and 0.250 inches

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Special Features:

Hardness rating 35.0 min and 43.0 maximum on lockwasher

Material:

Iron alloy 660 fastener

Material Specification:

Qq-w-423 federal specification single material response spring

Surface Treatment:

Passivate spring

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spring

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5305-01-156-5119

Panel Screw Assembly - Page 2 of 2

Fiig: A003b0

Mil-std (military Standard):

Mil-s-5059 spec.

