

View Online at <https://aerobasegroup.com/nsn/5305-01-156-6313>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.466 inches

**Fastener Length:**

Between 1.700 inches and 1.747 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.880 inches and 0.890 inches

**Grip Diameter:**

Between 0.4360 inches and 0.4370 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.111 inches first hole

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.438 inches

**Grip Length:**

Between 0.428 inches and 0.448 inches

**Thready Qty Per Inch (tpi):**

20

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.394 inches first hole and 1.431 inches first hole

**Material:**

Steel

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Mac p.S.1314 fscm 76301 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0