

View Online at <https://aerobasegroup.com/nsn/5305-01-156-6404>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.374 inches and 1.581 inches

**Fastener Length:**

Between 3.406 inches and 3.500 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.348 inches and 0.371 inches

**Width Between Flats:**

Between 0.798 inches and 0.812 inches

**Thread Diameter:**

0.562 inches

**Thready Qty Per Inch (tpi):**

12

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Hardness Rating:**

80.0 rockwell b

**Minimum Yield Strength:**

30000 pounds per square inch

**Material:**

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

2 type and 10p style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0