NSN 5305-01-157-1984



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-157-1984 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.313 inches and 0.363 inches **Fastener Length:** Between 0.635 inches and 0.665 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp e4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response **Screw Surface Treatment:** Aluminum and chromate **Screw Surface Treatment Specification:** Mil-c-83488 type 2 class 3 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Fiig:

No

A500d0

Demilitarization:

NSN 5305-01-157-1984

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.