NSN 5305-01-157-5634

Shoulder Screw - Page 1 of 2

Thread Class:

3a



View Online at https://aerobasegroup.com/nsn/5305-01-157-5634

Right-hand
Thread Length:
0.466 inches
Fastener Length:
2.046 inches
Head Style:
Pan no. 2
Head Diameter:
0.750 inches
Head Height:
0.266 inches
Shoulder Diameter:
0.497 inches first shoulder and 0.498 inches first shoulder
Shoulder Length:
1.505 inches first shoulder
Internal Drive Style:
W/o internal drive
Thread Diameter:
0.312 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
190000 pounds per square inch
Minimum Yield Strength:
Minimum Yield Strength: 170000 pounds per square inch
•
170000 pounds per square inch
170000 pounds per square inch Shoulder Shape:
170000 pounds per square inch Shoulder Shape: Round first shoulder
170000 pounds per square inch Shoulder Shape: Round first shoulder Special Features:
170000 pounds per square inch Shoulder Shape: Round first shoulder Special Features: Spring and ball positive locking
170000 pounds per square inch Shoulder Shape: Round first shoulder Special Features: Spring and ball positive locking Material:
170000 pounds per square inch Shoulder Shape: Round first shoulder Special Features: Spring and ball positive locking Material: Stainless steel
170000 pounds per square inch Shoulder Shape: Round first shoulder Special Features: Spring and ball positive locking Material: Stainless steel Material Specification:
170000 pounds per square inch Shoulder Shape: Round first shoulder Special Features: Spring and ball positive locking Material: Stainless steel Material Specification: Ams5643 assn standard single material response
170000 pounds per square inch Shoulder Shape: Round first shoulder Special Features: Spring and ball positive locking Material: Stainless steel Material Specification: Ams5643 assn standard single material response Surface Treatment:
170000 pounds per square inch Shoulder Shape: Round first shoulder Special Features: Spring and ball positive locking Material: Stainless steel Material Specification: Ams5643 assn standard single material response Surface Treatment: Passivate point
170000 pounds per square inch Shoulder Shape: Round first shoulder Special Features: Spring and ball positive locking Material: Stainless steel Material Specification: Ams5643 assn standard single material response Surface Treatment: Passivate point Surface Treatment Specification:

NSN 5305-01-157-5634

Shoulder Screw - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0