NSN 5305-01-157-7388

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-157-7388 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.578 inches and 0.682 inches **Fastener Length:** Between 0.720 inches and 0.750 inches **Head Style:** Pan **Head Diameter:** Between 0.594 inches and 0.615 inches **Head Height:** Between 0.203 inches and 0.218 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 18 **Hardness Rating:** 44.0 rockwell c primary washer and 48.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.620 inches and 0.640 inches **Primary Washer Style:** Spring tension **Primary Washer Material Thickness:** Between 0.052 inches and 0.060 inches **Material Specification:** Sae assn standard all material responses primary washer **Surface Treatment:** Zinc **Surface Treatment Specification:** G-4342-m, code 20u32, fscm 11862 mfr ref single treatment response **Thread Series Designator:** Unrc Shelf Life:

N/a **Unit Of Measure:** --

NSN 5305-01-157-7388

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0