NSN 5305-01-157-7398

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-157-7398

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.410 inches and 0.430 inches |
| Fastener Length: |
| 0.568 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.355 inches and 0.375 inches |
| Head Height: |
| Between 0.204 inches and 0.224 inches |
| Shoulder Diameter: |
| 0.215 inches first shoulder and 0.220 inches first shoulder |
| Shoulder Length: |
| 0.143 inches first shoulder and 0.153 inches first shoulder |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.164 inches |
| Width Across Flats: |
| Between 0.1562 inches and 0.1587 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Shoulder Shape: |
| Round first shoulder |
| Material: |
| Steel comp 302 or steel comp 303 |
| Material Specification: |
| Qq-s-763 federal specification 1st material response or astm a582 assn standard 2nd material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 type 1 or type 2 or type 3 federal specification single treatment response |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5305-01-157-7398

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0