100260

Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-158-6759

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.222 inches and 0.242 inches	
Fastener Length:	
Between 0.407 inches and 0.438 inches	
Head Style:	
Pan	
Head Diameter:	
Between 0.256 inches and 0.270 inches	
Head Height:	
Between 0.087 inches and 0.097 inches	
First Diameter From Head:	
Between 0.096 inches and 0.106 inches	
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	
Between 0.352 inches and 0.403 inches	
Internal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.138 inches	
Thready Qty Per Inch (tpi):	
32	
Externally Relieved Body Diameter Quantity:	
1	
Material:	
Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303	3se or steel comp 304 or steel comp 304l or
steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310	) or steel comp 310s or steel comp 314 or
steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347	or steel comp 348 or steel comp 384 or steel
comp 385	
Surface Treatment:	
Passivate	
Surface Treatment Specification:	
Qq-p-35 federal specification single treatment response	
Thread Series Designator:	
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	