NSN 5305-01-158-6760

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-158-6760 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** Between 0.719 inches and 0.750 inches **Head Style:** Pan **Head Diameter:** 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **First Diameter From Head:** Between 0.140 inches and 0.144 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.469 inches and 0.500 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a581 assn standard single material response or astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-01-158-6760

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0