

View Online at <https://aerobasegroup.com/nsn/5305-01-158-7820>

Thread Direction:

Right-hand

Thread Length:

Between 13.10 millimeters and 15.92 millimeters

Fastener Length:

Between 15.92 millimeters and 16.00 millimeters

Head Style:

Hexagon extended washer

Head Height:

Between 3.75 millimeters and 4.35 millimeters

Width Between Flats:

Between 6.78 millimeters and 7.00 millimeters

Extended Washer Diameter:

Between 8.50 millimeters and 9.20 millimeters

Extended Washer Thickness:

Between 0.75 millimeters and 1.00 millimeters

Washer Quantity:

1

Internal Drive Style:

W/o internal drive

End Application:

Truck, fire/crash p10; vehicle, commercial utility cargo (cucv)

Hardness Rating:

40.0 rockwell c primary washer and 50.0 rockwell c primary washer

Thread Pitch In Millimeters:

1.41

Primary Washer Outside Diameter:

Between 19.48 millimeters and 20.00 millimeters

Primary Washer Style:

Dome internal teeth

Primary Washer Material Thickness:

0.56 millimeters

Nonmachine Thread Diameter:

4.2 millimeters

Special Features:

Point style thread forming

Material:

Steel comp 1050 primary washer

Material Specification:

Sae assn standard single material response primary washer

Surface Treatment:

Phosphate primary washer

Surface Treatment Specification:

G-4435-m code a mfr ref single treatment response primary washer

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0