Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-159-2777

Thread Direction:
Right-hand
Thread Length:
16.2 millimeters
Fastener Length:
Between 19.20 millimeters and 20.00 millimeters
Head Style:
Hexagon
Head Height:
Between 4.1 millimeters and 4.7 millimeters
Width Between Flats:
Between 9.78 millimeters and 10.00 millimeters
Washer Quantity:
1
Thread Diameter:
6.0 millimeters
Hardness Rating:
40.0 rockwell c primary washer and 48.0 rockwell c primary washer
Thread Pitch In Millimeters:
1.0
Primary Washer Outside Diameter:
Between 12.07 millimeters and 12.50 millimeters
Primary Washer Style:
Spring tension
Primary Washer Material Thickness:
Between 1.5 millimeters and 1.8 millimeters
Material:
Steel
Material Specification:
Sae assn standard all material responses primary washer
Surface Treatment:
Phosphate
Surface Treatment Specification:
Gm 4435-m code a fscm 11862 mfr ref single treatment response
Thread Series Designator:
M
Shelf Life:
N/a
Unit Of Measure:
 Demiliterization
Demilitarization:
No

NSN 5305-01-159-2777

Assembled Washer Screw - Page 2 of 2

Fiig: A003b0

