

View Online at <https://aerobasegroup.com/nsn/5305-01-159-2779>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 18.7 millimeters and 20.3 millimeters

**Fastener Length:**

Between 24.20 millimeters and 25.80 millimeters

**Head Style:**

Flat top elevator

**Head Diameter:**

Between 8.6 millimeters and 9.8 millimeters

**Washer Quantity:**

1

**Internal Drive Style:**

Cross recess type 1

**Features Provided:**

Casehardened

**Hardness Rating:**

40.0 rockwell c primary washer and 50.0 rockwell c primary washer

**Nonmachine Thread Style:**

Gimlet point (type a, ab or ba)

**Countersink Angle:**

Between 80.0 radians and 82.0 radians

**Primary Washer Outside Diameter:**

Between 12.8 millimeters and 13.1 millimeters

**Primary Washer Style:**

Spring tension

**Primary Washer Material Thickness:**

Between 0.5 millimeters and 0.6 millimeters

**Nonmachine Thread Diameter:**

4.8 millimeters

**Material:**

Steel primary washer

**Material Specification:**

Gm 6010-m, fscm 11862 mfr ref single material response primary washer

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0