Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-159-2780

Thread Direction:
Right-hand
Thread Length:
25.0 millimeters
Fastener Length:
Between 38.70 millimeters and 41.30 millimeters
Head Style:
Flat top elevator
Head Diameter:
Between 6.82 millimeters and 7.35 millimeters
Washer Quantity:
1
Internal Drive Style:
Cross recess type ia
Thread Pitch In Millimeters:
1.41
Nonmachine Thread Style:
Gimlet point (type a, ab or ba)
Countersink Angle:
Between 90.0 degrees and 92.0 degrees
Primary Washer Outside Diameter:
Between 7.37 millimeters and 7.62 millimeters
Primary Washer Style:
Flat
Primary Washer Material Thickness:
Between 0.35 millimeters and 0.50 millimeters
Nonmachine Thread Diameter:
4.2 millimeters
Material:
Steel fastener
Material Specification:
Sae assn standard all material responses primary washer
Surface Treatment:
Zinc
Surface Treatment Specification:
Gm 4435-m code a fscm 11862 mfr ref single treatment response
Shelf Life:
N/a
Unit Of Measure:
 Demilitarization:
No

NSN 5305-01-159-2780

Assembled Washer Screw - Page 2 of 2

Fiig: A003b0

