NSN 5305-01-159-2780

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-159-2780 **Thread Direction:** Right-hand Thread Length: 25.0 millimeters Fastener Length: Between 38.70 millimeters and 41.30 millimeters **Head Style:** Flat top elevator **Head Diameter:** Between 6.82 millimeters and 7.35 millimeters Washer Quantity: **Internal Drive Style:** Cross recess type ia **Thread Pitch In Millimeters:** 1.41 Nonmachine Thread Style: Gimlet point (type a, ab or ba) **Countersink Angle:** Between 90.0 degrees and 92.0 degrees **Primary Washer Outside Diameter:** Between 7.37 millimeters and 7.62 millimeters **Primary Washer Style:** Flat **Primary Washer Material Thickness:** Between 0.35 millimeters and 0.50 millimeters **Nonmachine Thread Diameter:** 4.2 millimeters Material: Steel fastener **Material Specification:** Sae assn standard all material responses primary washer **Surface Treatment:** Zinc **Surface Treatment Specification:** Gm 4435-m code a fscm 11862 mfr ref single treatment response Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-159-2780

Assembled Washer Screw - Page 2 of 2



Fiig:

A003b0