NSN 5305-01-159-6552

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-159-6552 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.219 inches **Fastener Length:** 0.625 inches **Head Style:** Flat chamfer **Head Diameter:** 0.562 inches **Head Height:** 0.188 inches **First Diameter From Head:** 0.156 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.281 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Color black Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 **Material Specification:** Qq-s-763 federal specification 1st material response or astma582 assn standard 2nd material response or qq-s-763 federal specification 3rd material response or qq-s-763 federal specification 4th material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 military specification single treatment response **Thread Series Designator:** Unf Shelf Life:

--

N/a

Unit Of Measure:

NSN 5305-01-159-6552

Externally Relieved Body Screw - Page 2 of 2



Demi			

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.