## NSN 5305-01-159-6557

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-159-6557 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.469 inches and 0.484 inches **Fastener Length:** Between 0.501 inches and 0.548 inches **Head Style:** Pan **Head Diameter:** Between 0.838 inches and 0.863 inches **Head Height:** Between 0.286 inches and 0.304 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.438 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel comp 4037 or steel comp 8630 **Screw Material Specification:** Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 class 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A500d0

## NSN 5305-01-159-6557

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.