Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-159-6563



## Thread Class:

2a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

Between 0.639 inches and 0.750 inches

# Fastener Length:

0.750 inches

Head Style:

Hexagon

Head Height:

Between 0.208 inches and 0.230 inches

# Width Between Flats:

Between 0.489 inches and 0.500 inches

# Washer Quantity:

1

#### Internal Drive Style:

W/o internal drive

#### **End Application:**

Truck tractor, 5-to (m818, m931) truckcargodropside, 5-ton

# Thready Qty Per Inch (tpi):

18

## Hardness Rating:

45.0 rockwell c and 53.0 rockwell c

## Primary Washer Outside Diameter:

Between 0.540 inches and 0.556 inches

#### **Primary Washer Style:**

Split helical ring

## **Primary Washer Material Thickness:**

0.078 inches

# Material:

Steel

#### **Material Specification:**

Sae assn standard single material response fastener

## **Thread Series Designator:**

Unc

# Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5305-01-159-6563

Assembled Washer Screw - Page 2 of 2

Fiig: A003b0

