NSN 5305-01-160-1981



Thumbscrew - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-160-1981 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.380 inches **Fastener Length:** 1.810 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.980 inches and 1.020 inches **Head Height:** 0.250 inches **Shoulder Diameter:** 0.500 inches first shoulder **Shoulder Length:** 0.250 inches first shoulder **First Diameter From Head:** Between 0.170 inches and 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.180 inches **Point Style:** Flat **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity: Shoulder Shape:** Round first shoulder **Special Features:** Color black Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924 cl 4 military specification single treatment response

NSN 5305-01-160-1981

Thumbscrew - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.