## NSN 5305-01-160-4528

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-160-4528 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.995 inches and 1.065 inches **Fastener Length:** Between 2.070 inches and 2.130 inches **Head Style:** Flat chamfer **Head Diameter:** 0.940 inches **Head Height:** 0.210 inches **Shoulder Diameter:** 0.497 inches first shoulder and 0.509 inches first shoulder **Shoulder Length:** 1.065 inches first shoulder and 1.075 inches first shoulder **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 16 Hardness Rating: 28.0 rockwell c and 32.0 rockwell c **Shoulder Shape:** Round first shoulder **Special Features:** Thremo plastic strip type locking element in threads Material: Steel comp 1039 or steel comp 4037 **Surface Treatment:** Zinc **Surface Treatment Specification:** Gm 4342-m code 20u32 fscm 11862 mfr ref single treatment response **Thread Series Designator:** Unrc Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## **NSN 5305-01-160-4528** Shoulder Screw - Page 2 of 2



Fiig:

A003b0