## NSN 5305-01-160-5700

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-160-5700 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.338 inches and 0.388 inches **Fastener Length:** Between 1.348 inches and 1.378 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.360 inches and 0.374 inches **Head Height:** Between 0.115 inches and 0.125 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.990 inches and 1.010 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Surface Finish:** 32.0 microinches threads **Special Features:** 

Internal drive ribbed

#### Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735

### **Surface Treatment:**

Cadmium and chromate

#### **Surface Treatment Specification:**

Qq-p-416, type 2 cl 2 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

#### **Specification Data:**

80205-nas1578 professional/industrial association standard

# NSN 5305-01-160-5700

Close Tolerance Screw - Page 2 of 2



_					
C.	~~	14	I i	ife:	
J.	16			HE.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0