

View Online at <https://aerobasegroup.com/nsn/5305-01-161-2152>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.266 inches and 0.296 inches

Fastener Length:

Between 1.105 inches and 1.145 inches

Head Style:

Fillister

Head Diameter:

Between 0.290 inches and 0.330 inches

Head Height:

Between 0.118 inches and 0.130 inches

Internal Drive Style:

Cross recess type 1

Material Accommodated Thickness:

0.286 inches

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Special Features:

Quadruple lead threads

Material:

Steel comp 301 fastener or steel comp 302 fastener or steel comp 302b fastener or steel comp 303 fastener or steel comp 303se fastener or steel comp 304 fastener or steel comp 304l fastener or steel comp 305 fastener or steel comp 308 fastener or steel comp 309 fastener or steel comp 309s fastener or steel comp 310 fastener or steel comp 310s fastener or steel comp 314 fastener or steel comp 316 fastener or steel comp 316l fastener or steel comp 317 fastener or steel comp 321 fastener or steel comp 347 fastener or steel comp 348 fastener or steel comp 384 fastener or steel comp 385 fastener

Material Specification:

Qq-a-225/9 federal specification single material response stand-off

Surface Treatment:

Passivate primary washer

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response primary washer

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

Mil-std (military Standard):

Mil-c-5541 spec.