NSN 5305-01-161-2153

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-161-2153 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** Between 1.525 inches and 1.555 inches **Head Style:** Hexagon **Head Height:** Between 0.172 inches and 0.190 inches Width Between Flats: Between 0.367 inches and 0.375 inches **Material Accommodated Thickness:** 0.625 inches **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 175000 pounds per square inch **Special Features:** Hardness rating 35.0 min. And 43.0 max. On lockwasher; apply a solid filmlubricant to the screw threads only in accord with mil-l-8937 Material: Iron alloy 660 fastener **Material Specification:** Qq-w-423 federal specification single material response spring **Surface Treatment:** Passivate stand-off **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response stand-off **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

Fiig:

A003b0

NSN 5305-01-161-2153

Panel Screw Assembly - Page 2 of 2



Mil-std (military Standard):

Mil-s-5059 spec.