NSN 5305-01-161-6185

Panel Screw Assembly - Page 1 of 2



only in accord with mil-I-8937

View Online at https://aerobasegroup.com/nsn/5305-01-161-6185

Thread Cla	SS:
3a	
Thread Dir	ection:
Right-hand	
Thread Le	ngth:
0.365 inche	s
Fastener L	ength:
Between 1.	773 inches and 1.845 inches
Head Style	:
Hexagon	
Head Heig	ht:
Between 0.	172 inches and 0.190 inches
Width Bety	veen Flats:
Between 0.	367 inches and 0.375 inches
Material A	ccommodated Thickness:
0.625 inche	S
Thread Dia	meter:
0.250 inche	S
Thready Q	ty Per Inch (tpi):
28	
Min. Tensi	e Strength (psi):
175000 pou	inds per square inch
Special Fe	atures:
Hardness r	ating 35.0 min. And 43.0 max. On lockwasher; apply a solid film lubricant to the screw threads o
Material:	
Iron alloy 6	60 fastener
Material S	pecification:
Qq-w-423 f	ederal specification single material response spring
Surface Tr	eatment:
Passivate s	tand-off
Surface Tr	eatment Specification:
Qq-p-35 fe	leral specification single treatment response stand-off
Thread Se	ies Designator:
Unf	
Shelf Life:	
N/a	
Unit Of Me	asure:
Demilitariz	ation:
No	
Fiig:	
A003b0	

NSN 5305-01-161-6185

Panel Screw Assembly - Page 2 of 2

Mil-std (military Standard):

Mil-s-5059 spec.

