NSN 5305-01-161-9110

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-161-9110 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.343 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.058 inches and 0.068 inches **First Diameter From Head:** 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.126 inches and 0.157 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Finish color black Material: Steel comp 303 **Material Specification:** Astma108 assn standard single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-161-9110

Externally Relieved Body Screw - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.