

View Online at <https://aerobasegroup.com/nsn/5305-01-162-3961>

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 19.20 millimeters and 20.80 millimeters

**Head Style:**

Flat top elevator

**Head Diameter:**

Between 6.82 millimeters and 7.35 millimeters

**Washer Quantity:**

1

**Internal Drive Style:**

Cross recess type ii

**Nonmachine Thread Style:**

Gimlet point (type a, ab or ba)

**Countersink Angle:**

Between 90.0 degrees and 92.0 degrees

**Primary Washer Outside Diameter:**

Between 8.95 millimeters and 9.45 millimeters

**Primary Washer Style:**

Flat

**Primary Washer Material Thickness:**

Between 0.35 millimeters and 0.50 millimeters

**Nonmachine Thread Diameter:**

4.2 millimeters

**Material:**

Steel fastener

**Material Specification:**

Gsae military specification all material responses primary washer

**Surface Treatment:**

Phosphate

**Surface Treatment Specification:**

G-6047- (240) , fscm 11862 mfr ref single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

spec.