## NSN 5305-01-162-3963

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-162-3963



| Thread Class:  |
|--|
| 2a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 1.549 inches and 1.673 inches                                |
| Fastener Length:   |
| Between 1.688 inches and 1.750 inches                                |
| Head Style:  |
| Flat countersunk   |
| Head Diameter:   |
| Between 0.348 inches and 0.385 inches                                |
| Locking Feature:   |
| Pellet or strip or patch   |
| Internal Drive Style:  |
| Cross recess type 1  |
| Thread Diameter:   |
| 0.190 inches   |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Min. Tensile Strength (psi):   |
| 60000 pounds per square inch   |
| Countersink Angle:   |
| Between 99.0 degrees and 101.0 degrees                               |
| Screw Material:  |
| Steel  |
| Screw Material Specification:  |
| 66 federal standard single material response                         |
| Screw Surface Treatment:   |
| Cadmium and chromate   |
| Screw Surface Treatment Specification:                               |
| Qq-p-416 type 2 cl 2 federal specification single treatment response |
| Thread Series Designator:  |
| Unf  |
| Specification Or Standard:   |
| 3 type and 3c style  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |

No

## **NSN 5305-01-162-3963** Machine Screw - Page 2 of 2

Fiig: A500d0

