## NSN 5305-01-162-7884

N/a

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-162-7884 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.060 inches **Fastener Length:** 1.375 inches **Head Style:** Hexagon **Head Height:** Between 0.270 inches and 0.295 inches Width Between Flats: Between 0.551 inches and 0.562 inches Washer Quantity: **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating: 42.0 rockwell c primary washer and 48.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 1.115 inches and 1.135 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** Between 0.112 inches and 0.122 inches **Material Specification:** Sae assn standard all material responses primary washer **Surface Treatment:** Phosphate primary washer **Surface Treatment Specification:** Gm 4435-m code a type 72 fscm 11862 mfr ref single treatment response primary washer **Thread Series Designator:** Unrc Shelf Life:

## NSN 5305-01-162-7884

Assembled Washer Screw - Page 2 of 2



| ш | ın | 10 | <i>(</i> )+ | Measure: |  |
|---|----|----|-------------|----------|--|
|   |    |    |             |          |  |

--

Demilitarization:

No

Fiig:

A003b0