Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-162-7884

view online at https://defoballegroup.com/hsh/0000 01 102 7004
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
1.060 inches
Fastener Length:
1.375 inches
Head Style:
Hexagon
Head Height:
Between 0.270 inches and 0.295 inches
Width Between Flats:
Between 0.551 inches and 0.562 inches
Washer Quantity:
1
Internal Drive Style:
W/o internal drive
Thread Diameter:
0.375 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
130000 pounds per square inch
Hardness Rating:
42.0 rockwell c primary washer and 48.0 rockwell c primary washer
Primary Washer Outside Diameter:
Between 1.115 inches and 1.135 inches
Primary Washer Style:
Split helical ring
Primary Washer Material Thickness:
Between 0.112 inches and 0.122 inches
Material Specification:
Sae assn standard all material responses primary washer
Surface Treatment:
Phosphate primary washer
Surface Treatment Specification:
Gm 4435-m code a type 72 fscm 11862 mfr ref single treatment response primary washer
Thread Series Designator:
Unrc
Shelf Life:
N/a

NSN 5305-01-162-7884

Assembled Washer Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0