

View Online at <https://aerobasegroup.com/nsn/5305-01-162-7885>

Thread Direction:

Right-hand

Thread Length:

16.12 millimeters

Fastener Length:

Between 19.20 millimeters and 20.00 millimeters

Head Style:

Hexagon

Head Height:

Between 5.28 millimeters and 5.84 millimeters

Width Between Flats:

Between 12.73 millimeters and 13.00 millimeters

Washer Quantity:

1

Internal Drive Style:

W/o internal drive

Hardness Rating:

40.0 rockwell c primary washer and 48.0 rockwell c primary washer

Thread Pitch In Millimeters:

1.25

Nonmachine Thread Style:

Dog type (type b or c)

Primary Washer Outside Diameter:

Between 23.48 millimeters and 24.00 millimeters

Primary Washer Style:

Spring tension

Primary Washer Material Thickness:

Between 2.30 millimeters and 2.63 millimeters

Nonmachine Thread Diameter:

8.0 millimeters

Material:

Steel primary washer

Material Specification:

Sae assn standard all material responses primary washer

Surface Treatment:

Phosphate

Surface Treatment Specification:

Gm 6174-m, fscm 11862 mfr ref single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0