NSN 5305-01-162-9689

Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-162-9689



Thread Direction: Right-hand Thread Length: Between 14.88 millimeters and 18.40 millimeters Fastener Length: Between 17.70 millimeters and 18.40 millimeters **Head Style:** Hexagon **Head Height:** Between 4.04 millimeters and 5.09 millimeters Width Between Flats: Between 6.78 millimeters and 7.00 millimeters Washer Quantity: **Internal Drive Style:** W/o internal drive **Features Provided:** Casehardened **Thread Pitch In Millimeters:** 1.41 **Nonmachine Thread Style:** Gimlet point (type a, ab or ba) **Primary Washer Outside Diameter:** Between 16.57 millimeters and 17.00 millimeters **Primary Washer Style:** Flat **Primary Washer Material Thickness:** Between 1.6 millimeters and 2.3 millimeters **Nonmachine Thread Diameter:** 4.2 millimeters Material: Steel **Material Specification:** G-6010-m, fscm 11862 mfr ref single material response **Surface Treatment:** Chromium **Surface Treatment Specification:** G-4251-m code 59, fscm 11862 mfr ref single treatment response Shelf Life: N/a **Unit Of Measure:**

NSN 5305-01-162-9689

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0