NSN 5305-01-163-0589

Close Tolerance Screw - Page 1 of 2



Group

View Online at https://aerobasegroup.com/nsn/5305-01-163-0589

| Thread Class: |
|--|
| За |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.438 inches and 0.488 inches |
| Fastener Length: |
| Between 0.698 inches and 0.728 inches |
| Head Style: |
| Pan no. 2 |
| Head Diameter: |
| Between 0.360 inches and 0.374 inches |
| Head Height: |
| Between 0.115 inches and 0.125 inches |
| Grip Diameter: |
| Between 0.1890 inches and 0.1895 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.240 inches and 0.260 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Surface Finish: |
| 32.0 microinches threads |
| Special Features: |
| Internal drive ribbed |
| Material: |
| Titanium alloy |
| Material Specification: |
| Ams 4967 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas1578 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5305-01-163-0589

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

