

View Online at <https://aerobasegroup.com/nsn/5305-01-163-5747>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.220 inches and 0.312 inches

Fastener Length:

Between 0.282 inches and 0.312 inches

Head Style:

Pan

Head Diameter:

Between 0.256 inches and 0.270 inches

Head Height:

Between 0.087 inches and 0.097 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

80000 pounds per square inch

Screw Material:

Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347

Head Surface Treatment:

Paint

Screw Surface Treatment:

Passivate

Head Surface Treatment Specification:

595 no. 36231 federal standard single treatment response

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Color:

Gray

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0