## NSN 5305-01-163-5777

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-163-5777 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.588 inches and 0.688 inches **Fastener Length:** Between 0.658 inches and 0.688 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 190000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch **Special Features:** Double knurled head, diamond and straight Material: Steel **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 1 federal specification single treatment response **Thread Series Designator:** Unrf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-163-5777

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0