## NSN 5305-01-163-5790

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-163-5790

View Online at https://aerobasegroup.com/nsn/5305-01-163-5790					
Thread Class:					
3a					
Thread Direction	on:				
Right-hand					
Thread Length	:				
Between 0.338	inches and 0.388 inches				
Fastener Leng	th:				
Between 0.910	inches and 0.940 inches				
Head Style:					
Flat countersun	k				
Head Diameter	<del>:</del>				
Between 0.258	inches and 0.305 inches				
Grip Diameter:					
Between 0.1885	5 inches and 0.1895 inches				
Internal Drive	Style:				
Offset cruciform	(torque set)				
Thread Diamet	er:				
0.190 inches					
Grip Length:					
Between 0.552	inches and 0.572 inches				
Thready Qty Po	er Inch (tpi):				
32					
Min. Tensile St	rength (psi):				
160000 pounds	per square inch				
Hardness Ratio	ng:				
36.0 rockwell c	and 40.0 rockwell c				
Countersink A	ngle:				
Between 99.0 d	legrees and 101.0 degrees				
Surface Finish	:				
32.0 microinche	es threads				
Material:					
Steel comp e43	40 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150				
Surface Treatn	nent:				
Cadmium and	chromate				
Surface Treatn	nent Specification:				
Qq-p-416, type	2 cl 2 federal specification single treatment response				
Thread Series	Designator:				
Unjf					
Specification [	Oata:				
	professional/industrial association standard				
Shelf Life:					
NI/o					

N/a

## NSN 5305-01-163-5790

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0