## NSN 5305-01-163-5791

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-163-5791

View Online at https://aerobasegroup.com/nsn/5305-01-163-5791						
Thread Class:						
3a						
Thread Direction:						
Right-hand						
Thread Length:						
Between 0.378 inches and 0.428 inches						
Fastener Length:						
Between 1.388 inches and 1.418 inches						
Head Style:						
Flat countersunk						
Head Diameter:						
Between 0.464 inches and 0.507 inches						
Grip Diameter:						
Between 0.2485 inches and 0.2495 inches						
Internal Drive Style:						
Offset cruciform (torque set)						
Thread Diameter:						
0.250 inches						
Grip Length:						
Between 0.990 inches and 1.010 inches						
Thready Qty Per Inch (tpi):						
28						
Min. Tensile Strength (psi):						
160000 pounds per square inch						
Hardness Rating:						
36.0 rockwell c and 40.0 rockwell c						
Countersink Angle:						
Between 99.0 degrees and 101.0 degrees						
Surface Finish:						
32.0 microinches threads						
Material:						
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740						
Surface Treatment:						
Cadmium and chromate						
Surface Treatment Specification:						
Qq-p-416, type 2, class 2 federal specification single treatment response						
Thread Series Designator:						
Unjf						
Specification Data:						
80205-nas1580 professional/industrial association standard						
Shelf Life:						

N/a

## NSN 5305-01-163-5791

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0