

View Online at <https://aerobasegroup.com/nsn/5305-01-163-6471>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.453 inches and 0.547 inches

**Fastener Length:**

Between 0.453 inches and 0.547 inches

**Head Style:**

Button

**Head Diameter:**

Between 0.201 inches and 0.213 inches

**Head Height:**

Between 0.051 inches and 0.059 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.112 inches

**Width Across Flats:**

0.062 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 45.0 rockwell c

**Material:**

Steel comp 301

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Ams 2485 assn standard single treatment response or mil-c-13924 military specification single treatment response

**Supplementary Features:**

Non-magnetic electronic part

**Thread Series Designator:**

Unrc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.