

View Online at <https://aerobasegroup.com/nsn/5305-01-164-1127>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.159 inches and 1.209 inches

**Fastener Length:**

Between 4.021 inches and 4.051 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 1.643 inches and 1.793 inches

**Grip Diameter:**

Between 0.8730 inches and 0.8740 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.875 inches

**Grip Length:**

Between 2.842 inches and 2.862 inches

**Thready Qty Per Inch (tpi):**

14

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification single treatment response

**Thread Series Designator:**

Unf

**Specification Data:**

81205-bacb30lu manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.