

View Online at <https://aerobasegroup.com/nsn/5305-01-164-1604>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 25.1 millimeters and 28.7 millimeters

**Fastener Length:**

Between 28.70 millimeters and 31.30 millimeters

**Head Style:**

Hexagon

**Head Height:**

Between 4.37 millimeters and 4.83 millimeters

**Width Between Flats:**

Between 10.76 millimeters and 11.00 millimeters

**Washer Quantity:**

1

**Internal Drive Style:**

Hexagon

**Width Across Flats:**

Between 10.76 millimeters and 11.00 millimeters

**Hardness Rating:**

40.0 rockwell c primary washer and 60.0 rockwell c primary washer

**Thread Pitch In Millimeters:**

1.81

**Nonmachine Thread Style:**

Gimlet point (type a, ab or ba)

**Primary Washer Outside Diameter:**

Between 18.55 millimeters and 19.30 millimeters

**Primary Washer Style:**

Flat external and internal teeth

**Primary Washer Material Thickness:**

Between 0.80 millimeters and 1.00 millimeters

**Nonmachine Thread Diameter:**

6.3 millimeters

**Material:**

Steel

**Material Specification:**

Sae assn standard single material response primary washer

**Surface Treatment:**

Zinc primary washer

**Surface Treatment Specification:**

G-4342-m code 20u32 mfr ref single treatment response primary washer

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0