

View Online at <https://aerobasegroup.com/nsn/5305-01-164-1604>

Thread Direction:

Right-hand

Thread Length:

Between 25.1 millimeters and 28.7 millimeters

Fastener Length:

Between 28.70 millimeters and 31.30 millimeters

Head Style:

Hexagon

Head Height:

Between 4.37 millimeters and 4.83 millimeters

Width Between Flats:

Between 10.76 millimeters and 11.00 millimeters

Washer Quantity:

1

Internal Drive Style:

Hexagon

Width Across Flats:

Between 10.76 millimeters and 11.00 millimeters

Hardness Rating:

40.0 rockwell c primary washer and 60.0 rockwell c primary washer

Thread Pitch In Millimeters:

1.81

Nonmachine Thread Style:

Gimlet point (type a, ab or ba)

Primary Washer Outside Diameter:

Between 18.55 millimeters and 19.30 millimeters

Primary Washer Style:

Flat external and internal teeth

Primary Washer Material Thickness:

Between 0.80 millimeters and 1.00 millimeters

Nonmachine Thread Diameter:

6.3 millimeters

Material:

Steel

Material Specification:

Sae assn standard single material response primary washer

Surface Treatment:

Zinc primary washer

Surface Treatment Specification:

G-4342-m code 20u32 mfr ref single treatment response primary washer

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0