

View Online at <https://aerobasegroup.com/nsn/5305-01-164-1622>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.516 inches and 0.556 inches

Fastener Length:

Between 0.776 inches and 0.796 inches

Head Style:

Oval countersunk

Head Diameter:

Between 0.355 inches and 0.397 inches

Grip Diameter:

Between 0.2490 inches and 0.2495 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.250 inches

Grip Length:

Between 0.240 inches and 0.260 inches

Width Across Flats:

Between 0.1565 inches and 0.1587 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches threads

Special Features:

Three key slots 0.040 in. Min. And 0.044 in. Max. Dia. Evenly spaced and 0.681 in. Min. And 0.711 in. Max. Length

Material:

Iron alloy 660

Material Specification:

Ams 5732 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0