NSN 5305-01-164-1626



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-164-1626 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.016 inches and 1.066 inches **Fastener Length:** Between 4.401 inches and 4.431 inches **Head Style:** Flat countersunk **Head Diameter:** Between 1.404 inches and 1.538 inches **Grip Diameter:** Between 0.7480 inches and 0.7490 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.750 inches **Grip Length:** Between 3.365 inches and 3.385 inches Thready Qty Per Inch (tpi): 16 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response Qq-p-416 type 2 class 2 federal specification single treatment response

Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
--Demilitarization:

No

NSN 5305-01-164-1626

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.