## NSN 5305-01-164-5543

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-164-5543 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.425 inches **Fastener Length:** Between 1.847 inches and 1.877 inches **Head Style:** Oval countersunk **Head Diameter:** 0.397 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Internal Drive Style:** High-torque **End Application:** Aircraft, harrier av-8b **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.427 inches and 1.447 inches **Features Provided:** Cetyl alcohol lubricant Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 1.736 inches first hole and 1.756 inches first hole **Surface Finish:** 32.0 microinches threads Material: Steel comp xm-13

**Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate** 

## NSN 5305-01-164-5543

Close Tolerance Screw - Page 2 of 2



Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A003b0