## NSN 5305-01-164-5543

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-164-5543

Thread Class:
3a
Thread Direction:
Right-hand
0
Thread Length: 0.425 inches
Fastener Length: Between 1.847 inches and 1.877 inches
Head Style:
Oval countersunk
Head Diameter:
0.397 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Shank Unthreaded Hole Diameter:
0.076 inches first hole and 0.086 inches first hole
Internal Drive Style:
High-torque
End Application:
Aircraft, harrier av-8b
Thread Diameter:
0.250 inches
Grip Length:
Between 1.427 inches and 1.447 inches
Features Provided:
Cetyl alcohol lubricant
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
125000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Distance From Head Largest Bearing Surface To Shank Hole Center:
1.736 inches first hole and 1.756 inches first hole
Surface Finish:
32.0 microinches threads
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate

## NSN 5305-01-164-5543

Close Tolerance Screw - Page 2 of 2



Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0