## NSN 5305-01-164-8524

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

За

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-164-8524

oaa <b>-</b> 0.19
Between 0.251 inches and 0.301 inches
Fastener Length:
Between 0.386 inches and 0.416 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.221 inches and 0.279 inches
Grip Diameter:
Between 0.1365 inches and 0.1375 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.138 inches
Grip Length:
Between 0.115 inches and 0.135 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Data:
80205-nas1151 professional/industrial association standard

## NSN 5305-01-164-8524

Close Tolerance Screw - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0