NSN 5305-01-165-1282

Hexagon Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-165-1282
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 1.875 inches and 1.937 inches
Fastener Length:
Between 9.250 inches and 9.312 inches
Head Style:
Hexagon
Head Height:
Between 0.591 inches and 0.627 inches
Width Between Flats:
Between 1.469 inches and 1.500 inches
End Application:
Nsn 2320-01-097-0260 hemtt (heavy expanded mobility tactical truck)
Thread Diameter:
1.000 inches
Thready Qty Per Inch (tpi):
14
Min. Tensile Strength (psi):
150000 pounds per square inch
Hardness Rating:
33.0 rockwell c and 39.0 rockwell c
Minimum Yield Strength:
130000 pounds per square inch
Criticality Code Justification:
Feat
Special Features:
Weapon system essential
Material:
Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020
or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp
1527 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1536 or steel
comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541
Material Specification:
Sae j429 gr 8 assn standard all material responses
Surface Treatment:
Phosphate
Thread Series Designator:
Uns
Shelf Life:
N/a

Unit Of Measure:

NSN 5305-01-165-1282

Hexagon Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0