NSN 5305-01-165-1964

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-165-1964 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.406 inches **Fastener Length:** 1.188 inches **Head Style:** Flat countersunk **Head Diameter:** 0.381 inches **Grip Diameter:** 0.1885 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** 0.682 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 39.0 rockwell c and 43.0 rockwell c **Countersink Angle:** 100.0 degrees **Surface Finish:**

32.0 microinches grip

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

__

NSN 5305-01-165-1964

Close Tolerance Screw - Page 2 of 2



Demi			

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.