## NSN 5305-01-165-2461

Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-165-2461



3a Thread Direction: Right-hand Thread Length: Between 0.344 inches and 0.395 inches Fastener Length: Between 1.490 inches and 1.510 inches Head Style: Flat countersunk
Right-hand <b>Thread Length:</b> Between 0.344 inches and 0.395 inches <b>Fastener Length:</b> Between 1.490 inches and 1.510 inches <b>Head Style:</b>
Thread Length: Between 0.344 inches and 0.395 inches Fastener Length: Between 1.490 inches and 1.510 inches Head Style:
Between 0.344 inches and 0.395 inches <b>Fastener Length:</b> Between 1.490 inches and 1.510 inches <b>Head Style:</b>
Fastener Length: Between 1.490 inches and 1.510 inches Head Style:
Between 1.490 inches and 1.510 inches Head Style:
Head Style:
·
Flat countersunk
Head Diameter:
Between 0.502 inches and 0.507 inches
Grip Diameter:
Between 0.2487 inches and 0.2492 inches
Shank Unthreaded Hole Diameter:
0.076 inches first hole and 0.086 inches first hole
Internal Drive Style:
Hexagon
Thread Diameter:
0.250 inches
Grip Length:
Between 1.000 inches and 1.016 inches
Width Across Flats:
0.250 inches
Thready Qty Per Inch (tpi):
28
Countersink Angle:
100.0 degrees
Distance From Head Largest Bearing Surface To Shank Hole
1.391 inches first hole
Surface Finish:
63.0 microinches grip
Special Features:
Retaining element in shank
Material:
Steel comp xm-13
Material Specification:
Ams5629 assn standard single material response
Surface Treatment:
Passivate
Thread Series Designator:
Unjf

Center:

## NSN 5305-01-165-2461

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

