NSN 5305-01-165-2462

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-165-2462 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.431 inches and 0.481 inches **Fastener Length:** Between 1.441 inches and 1.471 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.449 inches and 0.507 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.990 inches and 1.010 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas 672 assn standard single treatment response **Thread Series Designator:** Unf **Specification Data:**

Shelf Life:

N/a

80205-nas2804 professional/industrial association standard

NSN 5305-01-165-2462

Close Tolerance Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0