

View Online at <https://aerobasegroup.com/nsn/5305-01-165-3259>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.375 inches

Fastener Length:

0.875 inches

Head Style:

Pan

Head Diameter:

Between 0.357 inches and 0.373 inches

Head Height:

Between 0.122 inches and 0.133 inches

First Diameter From Head:

Between 0.145 inches and 0.150 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.500 inches

Internal Drive Style:

Slot

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

55000 pounds per square inch

Externally Relieved Body Diameter Quantity:

1

Special Features:

Finish color black

Material:

Copper alloy 268 or copper alloy 260 or copper alloy 230 or copper alloy 377 or copper alloy 360 or copper alloy 353 or copper alloy 270 or copper alloy 274 or copper alloy 462 or copper alloy 464 or copper alloy 482 or copper alloy 485 or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 757 or copper alloy 764 or copper alloy 770 or copper alloy 240 or copper alloy 342

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-f-495 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-f-495 spec.